



**Make sure to visit
our Website**
<http://www.sefram.fr>

SEFRAM 7881

State-of-Art specifications for High Definition TV The feeling of a new way of measurement

Capabilities

- Panoramic LCD touch screen: **10 inches (16:9)**
- Display free to air programs for digital terrestrial, cable and satellite
- Display High Definition TV programs MPEG4-H264 and HEVC (H265)
- Display analogue TV programs
- All measurements for **DVB-T/T2, DVB-C/C2 (J83-A and B), DVB-S, DVB-S2, Wifi**
- Ultra fast spectrum analysis and expert spectrum analysis
- Checksat mode with NIT (satellite recognition)
- LTE function to help the diagnostic of filter
- Real time echoes and pre-echoes measurement with zoom
- Constellation diagram with zoom
- **Three in one display:** measurement, TV picture, mini spectrum
- Graphical display of measurements
- HDMI interface
- Analog input and output
- **Multistream capability**
- **Shoulder measurement**
- Memorize and export/import data with USB memory stick
- Battery with 1 hour charging time and 4 hours autonomy
- Supplied with **carrying bag and protection pouch**
- Weight: 2,8kg

NEW



**HEVC-H265
CAM CI**

The most complete TV Meter of the market

Time is money! With its fast and expert spectrum analysis, the checksat mode with NIT, the Cell ID function, real time echoes and pre-echoes, the MER per carrier, the constellation diagram, the fast Autoset, Multistream capability, the LTE function to help the diagnostic of spurious filtering, no doubt that you can setup a TV receiving system in record time.

Easy to use

Direct access to function from the touch screen is like a game: dedicated icons, special "home" function to go back to main menu, virtual keyboard to enter your specific data, possibility to export / import file on USB memory stick,... Getting started with the new SEFRAM 7881 is fast and easy.

A new design optimized for your safety

To protect your TV meter, we have design a robust metal housing with a protective pouch. For your safety, we supplied an ingenious system of belts and clip and a light transportation bag for non dedicated situation.

Panoramic touch screen

With the largest and brightest LCD of the market, using the new TV meter is possible in all conditions of light, including in sunny environment. With the 10.1" touch screen, you will use your new TV meter like a smartphone or a tablet: no need to worry where and which button to push, everything is displayed on the large screen in a clear and easy way. Incredibly user friendly!



Technical specifications		Terrestrial band				Satellite band	
Frequency							
Range	5-1005 MHz				900-2200 MHz		
Resolution	measurement: 50 kHz, display: 1 kHz				measurement: 1MHz, display: 1MHz		
Level measurements							
Dynamic range	20-120 dBµV				20-120 dBµV		
Noise floor level	10 dBµV typical				20 dBµV typical		
Units	dBµV, dBmV, dBm				dBµV, dBmV, dBm		
Accuracy	±2dB +/- 0.05dB/°C				±2dB +/- 0.05dB/°C		
Resolution	0,1dB				0,1dB		
Measurement filters	25kHz				125kHz		
Standards	BG, DK, I, L, MN, FM, DAB/DAB+, Porteuse, DVB-T/T2/T2lite, DVB-C/C2, J83B				PAL, SECAM, NTSC, Porteuse, DVB-S/S2, DSS		
Measurements RF, C/N, V/A							
Mesures numériques							
	DVB-T/H	DVB-T2/T2lite	DVB-C	DVB-C2	J83B	DVB-S, DSS	DVB-S2
Bit Error Rate (BER)	CBER (before Viterbi BER) VBER (after Viterbi BER) UNC (lost packets PER) Noise margin	LDPC (BER) BCH (BER) FER (frame error PER) Noise margin	BER (before Reed Solomon BER) UNC (lost packets PER) Noise margin	BER (before Reed Solomon BER) UNC (lost packets PER) Noise margin	BER (after Reed Solomon BER) UNC (lost packets PER) Noise margin	CBER (before Viterbi BER) VBER (after Viterbi BER) UNC (lost packets PER)	LDPC (BER) BCH (BER) PER Link margin Link margin
Modulation Error Rate (MER)	5 - 35dB	5 - 35dB	20 - 40dB	20 - 40dB	20 - 35dB	0-20dB	
MER per carrier	yes	yes	-	yes	-	-	
Symbol rate	-	-	1 to 7.224 Ms/s (J.83A)	-	1 to 5,563 Ms/s	1 to 45Ms/s	1 to 45Ms/s
Bandwidth	5, 6, 7, 8 MHz	1,7, 5, 6, 7, 8 MHz	-	6, 8 MHz	-	-	-
Mode	-	SISO, MISO, PLP simple or multiple	-	PLP simple or multiple, data slice	-	-	-
FFT size	2k and 8k, auto and manuel	1k, 2k, 4k, 8k, 16k and 32k + bandwidth extension, auto	-	4k	-	-	-
Constellation	QPSK, 16 and 64QAM, auto	QPSK, 16, 64 and 256QAM, auto	16, 32, 64, 128 and 256QAM	16, 64, 256, 1024, 4096QAM	64, 256QAM	QPSK	QPSK, 8PSK, 16APSK, 32APSK
Code rate	1/2, 2/3, 3/4, 5/6, 7/8 (auto)	1/2, 3/5, 2/3, 3/4, 4/5, 5/6 (auto)	-	2/3, 3/4, 4/5, 5/6, 8/9, 9/10	-	1/2, 2/3, 3/4, 5/6, 6/7, 7/8 (auto)	2/5, 1/2, 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 (auto)
Guard interval	auto and manuel	auto	-	auto	-	-	-
Inverted spectrum	auto	auto	auto	auto	auto	auto	auto
HP/LP	yes	-	-	-	-	-	-
PLP choice	-	yes	-	yes	-	-	-
Multistream	-	-	-	-	-	-	-
Standards	ETS 301-701	ETS 302-755	ITU J83-AppendixA	ETS 302-769	ETS 302-769	ETS 300-421	oui, PL descrambling ETS 302-307
Pre-echoes / Echoes / Impulse response							
Dynamic range	30 dB, 75km (en 8k)	50 dB, -75km +75km (en 8k)	-	50 dB, -5km +5km	-	-	-
Units	µs, km, miles	µs, km, miles	-	µs, km, miles	-	-	-
Constellation diagram	yes	yes	yes	yes	yes	yes	yes
Spectrum analysis							
Span	1MHz to full span in 1, 2, 5 sequences						
sweep time	100ms mini, 500 ms maxi						
Filters (automatic with selected span)	1,25k, 2,5k, 6,25k, 12,5k, 25k, 62,5k, 125k, 250k, 625kHz, 1,25MHz, 2,5MHz						
Attenuator	automatic ou manuel (0 to 50 dB with 10 dB steps)						
Dynamic (display)	60 dB (10 dB/div)						
With NIT(OSD) and TV picture	yes						
Measurement map							
Capacity	scrolling of 100 programs maximum						
Display	graphical (bargraph), tilt measurement						
Antenna Check mode							
Goal	fast antenna pointing				fast antenna pointing, single or double LNB		
Places/Satellites	30 places typical				30 satellites typical, with European database loaded		
NIT ckeck	yes ckeck 4 channels per place, can be modified by user				yes ckeck 4 channels per place, can be modified by user		
Signal Monitoring							
measurements	all, level and digital measurements						
duration	10mn, 60mn, 8h, 24h, 7d						
Memory							
Saving	internal non volatile memory, or USB memory stick (not supplied)						
Data	places, measure (level, BER/MER, frequency map, spectrums,...)						
Capacity	512 Kb (1000 files or folders max.)						
TV picture and sounds							
Analog programs	PAL, SECAM, NTSC						
Digital programs	MPEG2, MPEG4, HEVC, SD and HD definition						
Sounds	MPEG-1, MPEG-2, AAC, HE AAC, Dolby® Digital, Dolby® Digital Plus						
Encrypted programs (*)	yes						
RF input							
Input	75 Ohm, F and BNC with adaptor supplied						
Max permissive voltage	50 Vrms /50Hz						

Technical specifications	Terrestrial band	Satellite band
Remote supply and control		
Voltage	5V/13V/18 V/24V, 500 mA max (300mA pour 24V)	13/18 V, 500 mA max
DiSEqC	-	DiSEqC 1.2, dish rotor control, committed & uncommitted switches
Mini DiSEqC 22kHz)	-	22 kHz, ToneBurst
SatCR	-	DiSEqC protocol extension, control of 8 slots max.
DCSS	-	SatCR protocol extension, control of 32 slots max.
Aux Input/output		
Interfaces	USB A, Ethernet 10baseT (RJ45)	
Power supply input	jack 5.5 mm, 15 V max, 5 A max	
Audio/Video	HDMI output 720p, A/V jack for analog video input and earphones output	
Wi-Fi		
Functions	Wi-Fi network level measurement, SSID	
Frequency	2,4 and 5GHz	
WiFi antenna input	SMA reverse 50ohms, antenna	
General specifications		
Display	10.1 inches color LCD 16/9, backlight 500 cd/m ² , 1280x800 dots, capacitive touch pad	
Power supply	main adaptor 110/230 VAC, jack with 5,5mm diameter, 15 V/5 A	
Battery (non removable)	LiOn battery 100Wh	
Autonomy	4 hours typical	
Built-in charger	1 hour charging time for 80% capacity	
Operating temperature	-5°C to 45°C	
Storage temperature	-10°C to 60°C	
EMC and safety	NF-EN 61362-1 / NF-EN 61326-3 / NF-EN 61010-1	
Dimensions	310 x 210 x 80 mm	
Weight	2,8 kg (battery and pouch included)	

Supplied with: main adaptor (90-245V with European plug), user's manual on CD ROM, F/F and F/BNC adaptor, carrying protective pouch, belt clip, transportation pouch.

Optional accessories:

Car cigar lighter	P/N 978361000
Transportation hardcase	P/N 978852000
A/V cable	P/N 978852000



978852000
Transportation
handcase



978361000
Car cigar
lighter
adapter



978853000
Audio/video
cable

(*): the display of digital encrypted programs is possible, if user has a valid subscription card and if the encryption type is supported by the TV Meter. Please check with our sales department when ordering. **Dolby is a trade mark of Dolby Laboratories.**



FT7881 A00 - Specifications can be updated without notice




32, rue Edouard Martel - B.P. 55 - 42009 - St Etienne cedex 2
Tel. +33 (0).4.77.59 36 81
 Fax. +33 (0).4.77.57.23.23
 Website : www.sefram.fr - e-mail : sales@sefram.fr

For assistance and ordering

