

Sefram
Sefram

**Make sure to visit
our Website**

<http://www.sefram.fr>

SEFRAM 9802

Infrared thermometer and volt sense detector

Specifications

SEFRAM 9802

Temperature	-30°C to 500°C (-22°F to 932°F)
Résolution	0,2°C
Accuracy at 23°C ± 2°C < 80% RH	-30°C to 0°C (-22°F to 32°F) : ± 3°C (± 6°F) 1°C to 10°C (34°F to 50°F) : ± 2°C (± 4°F) 11°C to 40°C (52°F to 104°F) : ± 1.5°C (± 3°F) 41°C to 500°C (106°F to 932°F) : ±2°C (± 4°F) ou ±2.5% of reading, whichever is greater.
Display Resolution	0,2°C (0,5°F)
Response Time	0,5s
Réponse spectrale	6,5um to 18um
Emissivity	E=0,95
D:S	8:1 (calculated at 80% energy)
Repeatability	±1°C or ±0,5% of reading, whichever is greater.
Display Hold	10s
Weight / Dimension	40g / 20x30x100mm
Battery Life	150 hours (with laser)
Power	1 Pile 1.5 V AAA/LR03
Non-Contact Voltage	60VAC to 600VAC
Storage Temperature	-20°C à 60°C (without battery)

Supplied with: battery, using.

Capabilities

- Non-contact temperature measurement from -30° C to + 500° C
- Measurement display for 10s
- Continuous temperature measurement function
- Laser pointer
- LCD display
- Non-contact voltage detector from 60VAC to 600VAC
- Torch function



SEFRAM 9802



FT 9802 A 00- Specifications can be updated without notice

For assistance and ordering

Sefram



32, rue Edouard Martel - B.P. 55 - 42009 - St Etienne cedex 2
Tel. +33 (0).4.77.59 36 81
Fax. +33 (0).4.77.57.23.23
Website : www.sefram.fr - e-mail : sales@sefram.fr