

SA 100

2 cords with test tips $\varnothing 4$ mm, safety connection straight banana plug $\varnothing 4$ mm, black one and red one

Wire : PVC 0,75 mm²

Rated current : 12 A

Operating temperature : -20°C to +80°C

Safety : CAT II-1000 V and CAT III-600 V



SA 101

2 cords with test tips $\varnothing 4$ mm, safety connection right-angle banana plug $\varnothing 4$ mm, black one and red one

Wire : PVC 0,75 mm²

Rated current : 12 A

Operating temperature: -20°C to +80°C

Safety : CAT II-1000 V and CAT III-600 V



SA 105


2 cords with safety connection with straight banana plugs $\varnothing 4$ mm , black one and red one

Wire : PVC 0,75 mm²

Rated current : 12 A

Operating temperature : -20°C to +80°C

Safety : CAT IV-1000 V



SA 106

2 cords with safety connection right-angle and straight banana plugs $\varnothing 4$ mm , black one and red one

Wire: PVC 0,75 mm²

Rated current: 12 A

Operating temperature: -20°C to +80°C

Safety : CAT III-1000 V and CAT IV-600 V



SA 110

2 safety alligator clips $\varnothing 4$ mm, black one and red one

Rated current : 20 A

Operating temperature : -20°C to +80°C

Safety : CAT III-1000 V and CAT IV-600 V



SA 115

2 Test tips $\varnothing 4$ mm, $\varnothing 4$ mm safety connection, black one and red one

Rated current : 36 A

Operating temperature : -20°C to +80°C

Safety : CAT III-1000 V and CAT IV-600 V



SA 120

2 Flexible test clips with clamps, $\varnothing 4$ mm safety connection, black one and red one

Rated current : 6 A

Operating temperature : -20°C to $+80^{\circ}\text{C}$

Safety : CAT II-1000 V and CAT III-600 V



SA 151


2 cords with test tips $\varnothing 2$ mm, safety connection right-angle banana plug $\varnothing 4$ mm, black one and red one

Wire : PVC 0,75 mm²

Rated current : 12 A

Operating temperature : -20°C to $+80^{\circ}\text{C}$

Safety : CAT II-1000 V and CAT III-600 V




SA 155

2 Test tips $\varnothing 2$ mm, $\varnothing 4$ mm safety connection, black one and red one

Rated current : 16 A

Operating temperature : -20°C to $+80^{\circ}\text{C}$

Safety : CAT IV-1000 V



A 158

2 cords with test tips $\varnothing 4$, IP2X security retractable sleeve, right-angle plugs banana plugs $\varnothing 4$, one red and one black

length : 1 m

Wire : PVC 0,75 mm²

Rated current : 12A

Operating temperature : -20°C to $+80^{\circ}\text{C}$

Safety : CAT II-1000 V and CAT III-600 V



A 159

2 right-angle magnetic adapters, 6,6 mm diameter, $\varnothing 4$ mm safety connection, black one and red one

Rated current : 4 A

Operating temperature : -20°C to $+80^{\circ}\text{C}$

Safety : CAT III-1000 V and CAT IV-600 V



FT SAXXX A00 - Specifications can be updated without notice

Sefram

32, rue Edouard Martel - BP55- 42009 - St Etienne - cedex 2
Tél. +33 (0) 4.77.59.01.01 / Fax. +33 (0) 4.77.57.23.23
Web : www.sefram.com - e-mail : sales@sefram.com



For assistance and ordering